

Table 2. Commercial production liming table for target pH 5.6 -- rate in tons/ac.

Water pH	Buffer pH																			
	7.95	7.90	7.85	7.80	7.75	7.70	7.65	7.60	7.55	7.50	7.45	7.40	7.35	7.30	7.25	7.20	7.15	7.10	7.05	7.00
5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
5.4	0.0	0.0	0.0	0.0	0.0	0.0	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	1.0	1.0
5.3	0.0	0.0	0.0	0.0	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
5.2	0.0	0.0	0.0	0.5	0.5	0.5	0.5	0.5	0.5	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.5	1.5	1.5	1.5
5.1	0.0	0.0	0.5	0.5	0.5	0.5	0.5	0.5	1.0	1.0	1.0	1.0	1.0	1.5	1.5	1.5	1.5	1.5	1.5	2.0
5.0	0.0	0.0	0.5	0.5	0.5	0.5	0.5	1.0	1.0	1.0	1.0	1.5	1.5	1.5	1.5	1.5	2.0	2.0	2.0	2.0
4.9	0.0	0.0	0.5	0.5	0.5	0.5	1.0	1.0	1.0	1.0	1.5	1.5	1.5	1.5	2.0	2.0	2.0	2.0	2.5	2.5
4.8	0.0	0.5	0.5	0.5	0.5	1.0	1.0	1.0	1.0	1.5	1.5	1.5	2.0	2.0	2.0	2.0	2.5	2.5	2.5	2.5
4.7	0.0	0.5	0.5	0.5	0.5	1.0	1.0	1.0	1.5	1.5	1.5	2.0	2.0	2.0	2.0	2.5	2.5	2.5	3.0	3.0
4.6	0.0	0.5	0.5	0.5	1.0	1.0	1.0	1.5	1.5	1.5	2.0	2.0	2.0	2.5	2.5	2.5	3.0	3.0	3.0	3.5
4.5	0.0	0.5	0.5	0.5	1.0	1.0	1.5	1.5	1.5	2.0	2.0	2.0	2.5	2.5	2.5	3.0	3.0	3.5	3.5	3.5
4.4	0.0	0.5	0.5	1.0	1.0	1.0	1.5	1.5	2.0	2.0	2.5	2.5	2.5	3.0	3.0	3.5	3.5	3.5	4.0	4.0

NOTE: *To convert the lime rate from tons/ac to lbs/1000 square feet, multiply the lime rate by 50. A lime rate of 1.0 ton/ac would be equal to 50 lbs/1000 square feet.*